

IN THE CLAIMS:

Please amend the claims as follows:

- 5 1. (Currently Amended) An overload control method for use in a multi-branch Internet Protocol-based private branch exchange system within a network environment having a primary network and at least one alternate network, said method comprising the steps of:
- maintaining a congestion indicator status associated with each path in said  
 10 primary network, said congestion indicator status indicating whether said path is congested and based on congestion data from at least one end unit device that participated in a packet telephony communication;
- receiving a call set up request from a source terminal;
- determining if a primary path between said source terminal and a destination  
 15 terminal is congested using said congestion indicator status;
- routing said call using said at least one alternate network if said primary path between said source terminal and a destination terminal is congested; and
- setting a timer that will cause said congestion indicator ~~flag~~ status to  
 automatically expire after a predefined period of time, wherein said congestion indicator  
 20 status and said timer are reset each time said congestion data is received from said at least  
one end unit device and wherein said timer expires after a period of time within which said congestion is expected to be alleviated.
2. (Cancelled)
- 25 3. (Cancelled)
4. (Currently Amended) A congestion management method for use in an Internet Protocol-based private branch exchange system within a packet network environment, said  
 30 method comprising the steps of:

receiving congestion data from at least one end unit device that participated in a packet telephony communication;

determining if said congestion data indicates that a path associated with said packet telephony communication is congested;

5                    setting a congestion indicator flag associated with said path if said congestion data indicates that a path associated with said packet telephony communication is congested; and

                    setting a timer that will cause said congestion indicator flag to automatically expire after a predefined period of time, wherein said congestion indicator flag and said timer are reset each time said congestion data is received from said at least one end unit device and  
10 wherein said timer expires after a period of time within which said congestion is expected to be alleviated.

5.                    (Cancelled)

15

6.                    (Cancelled)

7.                    (Currently Amended) A congestion management method for use by an end unit packet phone adapter in a packet network environment, said method comprising the steps of:

20

collecting congestion data associated with a packet telephony communication;

determining if said packet telephony communication had a duration that exceeded a predefined threshold; and

reporting said congestion data to a centralized server that performs overload control, whereby said centralized server evaluates said congestion data to determine if a path associated with said packet telephony communication is congested; ~~and~~

25

~~setting~~ and sets a timer that will cause said determined congestion status to automatically expire after a predefined period of time, wherein said determined congestion status and said timer are reset by said centralized server each time said congestion data is reported and wherein said timer expires after a period of time within which said congestion is

30

expected to be alleviated.

8. (Cancelled)

5 9. (Cancelled)

10. (Currently Amended) A congestion manager for use in an Internet Protocol-based private branch exchange system within a packet network environment, comprising:

a memory for storing computer readable code; and

10 a processor operatively coupled to said memory, said processor configured to:  
receive congestion data from at least one end unit device that participated in a packet telephony communication;

determine if said congestion data indicates that a path associated with said packet telephony communication is congested;

15 set a congestion indicator flag associated with said path if said congestion data indicates that a path associated with said packet telephony communication is congested; and

maintain a timer that will cause said congestion indicator flag to automatically expire after a predefined period of time, wherein said congestion indicator flag and said timer

20 are reset each time said congestion data is received from said at least one end unit device and wherein said timer expires after a period of time within which said congestion is expected to be alleviated.

11. (Cancelled)

25 12. (Cancelled)